

With its classic and industrial appearance, our Corvo fits nicely in the entrance or hall of monumental buildings. Classic on the outside, but on the inside the Corvo is equipped with the most modern LED technology. You can choose from various options such as Tunable White. Also possible as a surface-mounted fixture.

CE

IP43

IK10



Specifications

Housing material	Stainless steel
Surface finish	Powder coated
Cover material	Acrylic
LED type	Samsung LM301B
Lifetime LED	L90B10 @ 100.000h, 25°C
Lifetime fixture	30 years
Voltage	230 V
CRI	≥ 80
Dimmable	DALI
Future proof	Yes
Net efficiency	148 Lumen/Watt



LIGHT

INTERNATIONAL

Typenumber	Dimensions	Lumen	Load	Weight
COR 1 3K B	As drawing	4.145 lm	28.2W	14kg
COR 2 3K B	As drawing	8.390 lm	56W	14kg
COR 3 3K B	As drawing	11.700 lm	78W	14kg
COR 1 27-50K B	As drawing	4.225 lm	30W	14kg
COR 2 27-50K B	As drawing	8.440 lm	56W	14kg

Colour black (RAL 9005) Standard (B)

Colour white (RAL 9016) Replace B for W

Colour grey (RAL 7035) Replace B for G

LED Colour temperature Replace 3K for 4K

Warranty 10 years

Country of origin The Netherlands

SROI > 25% of our production

Latest development 20/07/2023

LDT/IES file Download via website



LIGHT
INTERNATIONAL

